

SPECIFICATIONS	GP218-sw			
Configuration	2 × 18" vented subwoofer			
Transducers	8 ohm, 18" woofer with a 4" voice coil, ceramic magnet assembly			
Frequency Response (±3 dB)	31.4 Hz to 240 Hz (without processing)			
Frequency Range (-10 dB)	27.4 Hz to 1.2 kHz (without processing)			
Nominal Impedance	4 ohms			
Continuous Power Capacity	1700 W			
Recommended Power	3000 to 4000 W			
Sensitivity (1 W at 1 m)	101.5 dB			
Maximum Output - Continuous / Peak (SPL at 1 m)	134.5 dB / 140.5 dB			
Cabinet Type	Vented, rectangular enclosure			
Enclosure Material	Baltic birch plywood / 18 mm			
Finish	Finish available in black (GP218-sw-BK) or white (GP218-sw-WH)			
Grille	14 gauge powder coated steel			
Connectors	Two NL4 in parallel			
Pin Outs	<table><tr><td>Pins</td></tr><tr><td>1+/1-Sub</td></tr><tr><td>2+/2-NC</td></tr></table>	Pins	1+/1-Sub	2+/2-NC
Pins				
1+/1-Sub				
2+/2-NC				
Attachment Points	Sixteen (16) threaded M10 inserts			
Weight	191 lb / 86.6 kg Net 209 lb / 94.8 kg Shipping			
Dimensions (HWD) inches	20 x 47.17 x 30			
Dimensions (HWD) mm	508 x 1198 x 762			
Accessories Available (optional)	CRT-218-0 Wood cart CVR-GP218 Cover			

All specifications are subject to change without notice.

Specifications	GP-118sw
Frequency Response (-10 dB)	29 Hz–800 Hz
Power Capacity ¹	850 W (82.5 V) continuous 1700 W peak
Nominal Sensitivity ²	98 dB, 2.83 V @ 1 m
Maximum Rated SPL	129 dB @ 1 m, continuous ³ 135 dB @ 1 m, peak ⁴
Nominal Impedance	8Ω
Transducer	457 mm (18-inch) driver with 102 mm (4-inch) voice coil
Recommended Power	1700 W / 6800 W / 82 V
Enclosure Details	
Input Connector	Dual NL4 connector
Pinout	1+/1- Sub 2+/2- N/C
Enclosure Material	18 mm Baltic birch plywood
Finish	Black (GP118-sw-BK) or white (GP118-sw-WT) texture coat
Attachment Points	16 threaded M10 inserts
Grille	16-gauge powder coated steel
Dimensions (HWD) inches	20.9 x 25.8 x 30.4
Dimensions (HWD) mm	531 x 656 x 772
Net Weight	111 lb / 50.3 kg
Shipping Weight	121 lb / 54.9 kg

All specifications are subject to change without notice.

SPECIFICATIONS	GP212-SW			
Configuration	2 x 12" - 4th order band-pass subwoofer			
Transducers	2 x 550 W, 8 ohm 12" woofer with a 4" voice coil, ceramic magnet assembly			
Frequency Response (±3 dB)	40 Hz - 100 Hz (without processing)			
Frequency Range (-10 dB)	32 Hz - 107 Hz (without processing)			
Nominal Impedance	4 ohms			
Continuous Power Capacity	1100 W			
Recommended Power	1650–2200 W			
Sensitivity (1 W at 1 m)	99 dB			
Maximum Output—Continuous / Peak (SPL at 1 m)	129.4 dB / 135.4 dB			
Cabinet Type	4th-order bandpass			
Enclosure Material	15mm Baltic birch plywood			
Finish	Available in Black (GP212-sw-BK) or white (GP212-sw-WH)			
Connectors	2 x NL4 in parallel			
Pinout	<table><tr><td>Pins</td></tr><tr><td>1+/1-Sub</td></tr><tr><td>2+/2-NC</td></tr></table>	Pins	1+/1-Sub	2+/2-NC
Pins				
1+/1-Sub				
2+/2-NC				
Attachment Points	Six threaded M10 inserts			
Weight	99.5 lb / 45.1 kg net 115.5 lb / 52.4 kg shipping			
Dimensions (HWD) inches	15 x 20 x 29			
Dimensions (HWD) mm	381 x 508 x 737			
Accessories Available (optional)	CVR212-2 Cover CP212-0 – Wood cart			
All specifications are subject to change without notice.				