

SPECIFICATIONS	WL3082	WL212-sw
Configuration	Dual 8", 3-way, triamp line-array	Dual 12", 4th-order bandpass subwoofer
Transducers		
High-frequency	1.4" exit, 3" diaphragm, neodymium magnet compression driver	-
Low-frequency	Dual, 8" woofer, 2.5" voice coil	Dual, 12" woofer with a 4" voice coil, ceramic magnet assembly
Frequency Response (±3 dB)	68 Hz - 18 kHz	40 Hz - 100 Hz
Frequency Range (-10 dB)	62 Hz - 20 kHz	32 Hz - 107 Hz
Nominal Impedance	HF: 16 ohms MF: 16 ohms LF: 16 ohms	SUB: 4 ohms
Continuous Power Capacity ¹	HF: 85 W MF: 250 W LF: 250 W	LF: 1100 W
Maximum Output, Continuous / Peak (dB SPL at 1 m)	HF: 127 dB SPL / 133 dB SPL MF: 122 dB SPL / 128 dB SPL LF: 122 dB SPL / 128 dB SPL	LF: 129 dB SPL / 135 dB SPL
Nominal Coverage	H: 140° V: dependent on number of elements used	- -
Enclosure Type	Ported, trapezoidal	4th-order bandpass
Enclosure Material	15 mm birch plywood	15 mm birch plywood
Finish	Available in black (WL3082-BK) or white (WL3082-WH)	Available in black (WL212-sw-BK) or white (WL212-sw-WH)
Grille	Perforated, 16AWG steel, backed with black/white cloth fabric	-
Connectors	Two NL8 in parallel	Two NL8 in parallel
Pin Outs	1+/1- NC 2+/2- LF 3+/3- MF 4+/4- HF	1+/1- Sub 2+/2- NC 3+/3- NC 4+/4- NC
Attachment Points	Integral, side plate adjustable rigging system, vertical splay adjustable in 1° increments from 0° - 10°	Integral, non-adjustable
Weight (Net)	38 lb / 17 kg	109 lb / 49.4 kg
Weight (Shipping)	45.5 lb / 20.7 kg	125 lb / 56.7 kg
Dimensions (HWD) inches	9 × 20 × 16	15 × 20 × 29
Dimensions (HWD) mm	229 x 508 x 406	381 x 508 x 737
Available Accessories	AF3082-L AF3082-S CVR3082-4 Cover CP3082-CT Wood cart EB3082 PB3082	AF3082-L AF3082-S CP212-O Wood cart EB3082

¹ Two hours, IEC specified noise

SPECIFICATIONS	GP212-SW			
Configuration	2 x 12" - 4th order band-pass subwoofer			
Transducers	2 x 550 W, 8 ohm 12" woofer with a 4" voice coil, ceramic magnet assembly			
Frequency Response (±3 dB)	40 Hz - 100 Hz (without processing)			
Frequency Range (-10 dB)	32 Hz - 107 Hz (without processing)			
Nominal Impedance	4 ohms			
Continuous Power Capacity	1100 W			
Recommended Power	1650–2200 W			
Sensitivity (1 W at 1 m)	99 dB			
Maximum Output—Continuous / Peak (SPL at 1 m)	129.4 dB / 135.4 dB			
Cabinet Type	4th-order bandpass			
Enclosure Material	15mm Baltic birch plywood			
Finish	Available in Black (GP212-sw-BK) or white (GP212-sw-WH)			
Connectors	2 x NL4 in parallel			
Pinout	<table><tr><td>Pins</td></tr><tr><td>1+/1-Sub</td></tr><tr><td>2+/2-NC</td></tr></table>	Pins	1+/1-Sub	2+/2-NC
Pins				
1+/1-Sub				
2+/2-NC				
Attachment Points	Six threaded M10 inserts			
Weight	99.5 lb / 45.1 kg net 115.5 lb / 52.4 kg shipping			
Dimensions (HWD) inches	15 x 20 x 29			
Dimensions (HWD) mm	381 x 508 x 737			
Accessories Available (optional)	CVR212-2 Cover CP212-0 – Wood cart			
All specifications are subject to change without notice.				